

Novaflex

Corrugated Dock Hose

Novaflex 3265 Corrugated Dock Hose

Specially designed for barge unloading where flexibility and ease of handling are required. Special tire cord reinforcement with dual wire helix and corrugated cover enhances the characteristics.

Construction:

Tube: NBR

Reinforcement: Polyester tire cord, dual wire helix.

Cover: Black NBR/PVC corrugated

Ends: Straight.

Length 100 ft (max)

Temperature range: -30°F to +200°F



Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3265-06000-00	6	7.20	4	30	30"	225	7.20
3265-08000-00	8	9.30	6	42	30"	225	10.84
3265-10000-00	10	11.50	6	60	30"	225	13.40
3265-12000-00	12	13.80	8	72	30"	225	17.25

Meets USCG requirements

Ajax, ON
Indianapolis, IN
Haw River, NC
Berlin, NJ

Tel 905.686.5200
Tel 317.334.1444
Tel 336.578.2161
Tel 856.768.2275

Fax 905.686.8349
Fax 317.334.1535
Fax 336.578.5554
Fax 856.768.2385

800.526.6288
800.334.4270
800.225.0215

THE
NOVAFLEX
GROUP 