

Novaflex®

Molten Sulphur Hose

Molten Sulphur Hose Novaflex 5500BE

Novaflex Molten Sulphur 5500BE is made for use in loading and unloading barges, ships and tank trucks. This is an engineered hose designed with a special high temperature EPDM tube with built in nipples and flanges.

Specifications

Tube: Special High Temperature EPDM

Reinforcement: Multiple plies of polyester tire cord with helix

Cover: Black EPDM

Operating Temperature: 300°F (intermittent to 350°F)

Branding: 5500 Molten Sulphur Suction and Discharge,
200 PSI Max WP, 300°F Max Temp (intermittent to 350°F)



Specification Chart

Product No	ID"	OD"	WP	MBR	Wt/Ft
5500BE-06000-00	6	7.87	200	42	10.8lbs
5500BE-08000-00	8	10.15	200	54	17.4lbs
5500BE-10000-00	10	12.30	200	72	25.5lbs

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation.

02.2016

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IND 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk