

Novaflex®

Flour Discharge Hose

Novaflex 6201

Flour Discharge Hose (3/16" tube)

Designed for the transfer of dry edible food products such as sugar, flour, beans etc. This ultra smooth microbe resistant tube is built on special stainless steel mandrels for cleanliness.

Construction:

Tube: White FDA natural rubber.

Reinforcement: Plies of polyester synthetic textile with static wire.

Cover: Black SBR high grade weather and abrasion resistant rubber

Length: 100 ft.

Temperature Range: -40°C to +41°C



Specification Chart

Part No.	ID in	ID mm	OD in	OD mm	PSI	WP Bar	MBR in	MBR cm	Kg/m
6201WG-03000-00	3	76.2	3.67	93.2	100	6.90	n/a	n/a	2.90
6201WG-04000-00	4	101.6	4.69	119.1	100	6.90	n/a	n/a	3.72
6201WG-05000-00	5	127	5.73	145.5	100	6.90	n/a	n/a	4.99

Due to continuous improvements, technical data subject to change without notice. All hose and duct manufactured by Novaflex® are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. For complete guide to proper care, use and maintenance see Care & Maintenance Guide @2003-1 at www.novaflex.com. Please defer to Novaflex terms and conditions of sale located at: www.novaflex.com/TermsConditions/

02.2014

IN U.K.

Bromborough, Wirral

18 Plantation Park 2, Power Road
Bromborough, Wirral UK CH62 3QT
tel 44(0)151-334-0873
fax 44(0)151-334-7145
www.novaflex.co.uk Email: sales@novaflex.co.uk

IN CANADA

Ajax, Ontario

555 Beck Crescent
Ajax, ON L1Z 1C9
tel (905)686-5200
fax (905) 686-8349
800-563-3539

IN USA

North Carolina

449 Trollingwood Road
Haw River, NC 27258
tel (336)578-2161
fax (336)578-5554
800-334-4270

New Jersey

1024 Industrial Drive
West Berlin, NJ 08091
tel (856)768-2275
fax (856)768-2385
800-225-0215

Indianapolis

7812 Moller Road
Indianapolis, IN 46268
tel (317)334-1444
fax (317)334-1535
800-526-6288