

UHMW Tube EPDM Food Suction & Discharge Hose

Novaflex 6403 UHMW Tube EPDM Food Suction & Discharge Hose

Recommended for special applications that require smooth tubes and easy to clean surfaces. Recommended for the food transfer application that demands flexibility and ruggedness with a clean white FDA ultra high molecular weight polyethylene grade tube. This food grade tube is odorless and tasteless for all those all purpose transfer applications. This ultra smooth microbe resistant tube is built on special stainless steel mandrels for cleanliness.

Construction:

Tube: FDA UHMW - odor and tasteless

Reinforcement: Multiple plies of polyester tire cord with helix wire

Cover: Gray EPDM

Length: 100ft

Temperature Range: -40°F to +225°F (Cleaning In Place to 248°F) Not for continuous steam service



Part No.	I.D.	O.D.	Max WP psi	Bend Radius	Vacuum HG	WT LBS/FT
6403CU-00750-00	¾	1.19	200	3.5	29"	0.58
6403CU-01000-00	1	1.44	200	3.5	29"	0.63
6403CU-01500-00	1½	2.02	200	4	29"	1.06
6403CU-02000-00	2	2.52	200	6	29"	1.33
6403CU-03000-00	3	3.55	200	9	29"	2.12
6403CU-04000-00	4	4.55	200	12	29"	2.83

It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. Due to continuous improvements, technical data is subject to change without notice.

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
 Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
 Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
 Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX[®]
 GROUP 

Email: sales@novaflex.com
 Website: www.novaflex.com