

High Pressure Superior Quality Brewery Discharge Hose

Novaflex 6502 (New, Heavier Design) High Pressure, Superior Quality Brewery Discharge Hose

The unique construction of Novaflex 6502 provides maximum flexibility for ease of handling. The special smooth chlorobutyl bacteria resistant tube designed for non-oily products will not impart odor or taste. Meets FDA, USDA and 3-A (Cert# 1376).

Construction:

Tube: White chlorobutyl
Reinforcement: Multiple plies of polyester tire cord
Cover: Red EPDM
Length 100 ft
Temperature Range: -40°F to +240°F (Cleaning In Place to 248°F)
Not for continuous steam service.



Part No.	I.D.	O.D.	Plies	Max WP psi	MBR	Weight lb/Ft
6502WB-00750-00	¾	1.25	4	350	n/a	0.4
6502WB-01000-00	1	1.5	4	350	n/a	0.5
6502WB-01500-00	1½	2.0	4	350	n/a	0.71
6502WB-02000-00	2	2.50	6	350	n/a	1.25
6502WB-02500-00	2½	3.02	6	350	n/a	1.55
6502WB-03000-00	3	3.52	6	350	n/a	1.86
6502WB-04000-00	4	4.52	6	350	n/a	2.28

06.2015

Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
GROUP 

Email: sales@novaflex.com
 Website: www.novaflex.com